

ROLLING SLIDE PARTS

Publication number: JP10047334

Publication date: 1998-02-17

Inventor: KADOKAWA SATOSHI; MURAKAMI YASUO

Applicant: NIPPON SEIKO KK

Classification:

- **International:** *F16H53/06; C21D9/40; F16C3/02; F16H53/00; C21D9/40; F16C3/02; (IPC1-7): F16C3/02; C21D9/40; F16H53/06*

- **European:**

Application number: JP19960204588 19960802

Priority number(s): JP19960204588 19960802

Report a data error here

Abstract of JP10047334

PROBLEM TO BE SOLVED: To ensure durability and wear resistance by regulating the quantity of carbide in a surface layer, hardness, the decomposition ratio of residual austenite associated with surface reinforcing work and surface roughness respectively to the specific value. **SOLUTION:** This rolling slide part is used in the state of coming in rolling contact or sliding contact with another opposed part. In the case where a range of 0-50 μ m in depth from the surface is made a surface layer part, the rate of carbide contained in this surface layer is 10-25vol%, the decomposition ratio of residual austenite of the surface layer part to the initial value is 1/10-3/10, the hardness of the surface layer part is Hv830-Hv960, and surface roughness is 25 μ m. Sufficient durability and wear resistance can thereby be ensured even under such a severe condition as to be lubricated only by lubricating oil with soot and other insoluble components mixed therein.

Data supplied from the *esp@cenet* database - Worldwide